



CONTROL SIGNALLING DEVICES AND ACCESSORIES



07

General characteristics

Our control and signalling units are designed to ensure accuracy, reliability, high mechanical and electrical life. All pushbuttons are certified IP65 (IP66 with optional dustproof cover), while foot switches are IP54. The contact blocks are equipped with maximum 4 contacts with rating up to 10 A each. The NC contacts are made to guarantee positive opening for safety function. The terminal screws with self-raising plate are supplied in open position for an easier and quicker wiring operation.




■ Thermoplastic foot switches

(IP54)



Without protection




Code	Description		Pack	Weight (kg)
PSI00M20	Thermoplastic foot switches without protection		1	0,749



With protection

(IP54)




Code	Description		Pack	Weight (kg)
PCI00M20	Thermoplastic foot switches with protection w/o lock		1	1,034
PCI00PIM20	Thermoplastic foot switches with protection with lock		1	1,024

Metal foot switches



(IP54)


Without protection

Contact element	Code	Description	Pack	Weight (kg)
	PSA00M20	Metal foot switches w/o protection and w/o lock	1	1,328



(IP54)

With protection

Contact element	Code	Description	Pack	Weight (kg)
	PCA00M20	Metal foot switches protection and w/o lock	1	1,969
	PCA00PIM20	Metal foot switches with protection and with lock	1	1,981

Contact block

Code	Description	Pack	Weight pack (kg)
KIT00	Additional contact block 00 kit for foot switches	5	0,343
ELEM00	Contact block 1NO+1NC snap action	5	0,495
ELEM01	Contact block 1NO+1NC slow action	5	0,485